



Hiboost vehicle booster C27-5S-EU

Description

HiBoost Vehicle booster C27-5S-EU is a 50dB, ultra cell phone signal booster that provides a complete solution for all vehicles. Improve 2G, 3G and 4G cell phone signal strength for voice and data, especially in poor signal areas. With standardized industrial level design, strict testing and competitive pricing, the C27-5S-EU provides a superior communication experience with clearer calls and faster data speeds than ever before.



Key Features

- Supports all 2G, 3G and 4G bands
- Streamlined design
- Quality metal construction, strong and durable
- Good heat dissipation for longevity
- Low interference to cell tower
- Multiple users are supported
- CE certified



Standard Kit Includes

- C27-5S-EU mobile signal booster
- Outdoor magnetic antenna
- Indoor Patch antenna
- Input DC 12-24V, output 5V/3A cigarette lighter with 1.8m USB power cable





Specification

RF Parameter	Uplink	Downlink	
Frequency Range	800MHz	832~862MHz	791~821MHz
	900MHz	880~915MHz	925~960MHz
	1800MHz	1710~1785MHz	1805~1880MHz
	2100MHz	1920~1980MHz	2110~2170MHz
	2600MHz	2500~2570MHz	2620~2690MHz
Max .Gain	45dB	50dB	
Electrical Parameter			
Power Adapter	Input DC 12~24V, output DC 5V/3A		
Input & Output Impedance	50 ohm		
Mechanical Parameter			
I /O Port Type	SMA-Female		
Environment Parameter			
Operating Temperature	-45°C~+55°C		
Storage Temperature	-40°C~+80°C		
Relative Humidity	95%		
Barometric Pressure	55 kPa - 106 kPa		
Environment Conditions	IP40		